


Status 08/23	Technical Data	
Electric Submersible Pump		HUDIG®
HC 37 ST, HC 37 SA		



HC 37 ST



Application:

For use in the building trade, in industry and in local authorities.

Design features:

Electric submersible pump with double casing. Impeller made of wear-resistant polyurethane, double mechanical seal made of silicon carbide. The double-jacket cooling system allows for continuous submerged and slurping operation.

The pump can be equipped with a float switch for operation with highly variable inflow quantities.

Technical Data:

Protection class:	IP68
Immersion depth	max. 10 m
Rubber hose cable (electrical connection cable)	10 m H07RN-F3G 1.0 mm²
Jacket:	Stainless steel
Pump Housing:	1.4301 GG20
Shaft:	Stainless steel
Impeller:	1.4406
Bolts + screws:	Polyurethane
Mechanical seals:	1.4301
Orings:	Carbon/Ceramic + SIC/SIC NBR

Accessories:

Hoses,
Motor protection plug

HC 37 SA:

incl. float switch

Type	Pressure outlet		Motor power	Frequency	Voltage 1-phase	Speed	Rated current	Delivery height max.	Conveyor quantity max.	Sieve opening	Dimensions mm			Weight kg
	mm	R"AG									l	w	h	
HC 37 ST	50	2"	0.37	50	230	2850	3.0	10	240	6	197	186	310	13

Subject to technical changes!