

BENDER P26



Dimensions

Effective	80 x 85 x 95h.
On Pallet	80 x 85 x 115h.

Weight

Effective	Kg. 320
On Pallet	Kg. 350
Grease Red Quality	8 lt
Electric Motor	Special Voltage 230/400 volt 50 Hz/3 phase
	2,5 HP / 1,85 KW
Turns / Minute	13
Rotating plate	Dia.275mm

R. = 45 Kg. / mm²

- 1 BAR Ø 26
- 2 BARS Ø 22
- 3 BARS Ø 18

R. = 65 Kg. / mm²

- 1 BAR Ø 24
- 2 BARS Ø 16
- 3 BARS Ø 12

R. = 80 Kg. / mm²

- 1 BAR Ø 22
- 2 BARS Ø 14
- 3 BARS Ø 10

Our Bender **P26** offers to the operator the possibility to open the working cover easily, to clean / check the interior parts without difficulties. Turning disk and four long adjustable saddles in 38NCD4 special steel. As preparation of the machine for the transport, we set it on a pallet (standard measures), cover it with a stiff carton paper and with a cellophane coat, and then fix it with plastic band.

Standard Equipments

- 3 AXEL KEYS: (6 mm - 8 mm - 17 mm)
- 1 BUSH Ø 50 (cod. 194180) 1 BUSH Ø 60 (cod. 194190)
- 1 BUSH Ø 70 (cod. 194200) 1 BUSH Ø 80 (cod.194210)
- 3 BUSH HOLDING PINS (cod. 194030)
- 1 STIRRUP PIN (cod. 194040)
- 1 SQUARE PIN (cod. 194090)
- 1 CHECKING BLOCK (cod. 195170)
- 1 PEDAL not C.E. (cod. 181090)

