

BENDER D32



Dim	ensions
Effective	80 x 85 x 95h.
On Pallet	80 x 85 x 115h.
V	/eight
Effective	Kg. 320
On Pallet	Kg. 350
Grease Red Quality	8 lt
Electric Motor	Special Voltage 230/400 volt/50 Hz/3 phase
	3 HP / 2 KW
Turns / Minute	5
Rotating plate	Dia.275mm
4E Va / mm2	D - 90 Va /mm2

R. = 45 Kg. / mm2 1 BAR Ø 32 2 BARS Ø 28 3 BARS Ø 22 R. = 65 Kg. / mm2 1 BAR Ø 28 2 BARS Ø 22 3 BARS Ø 18 R. = 80 Kg. / mm2 1 BAR Ø 22 2 BARS Ø 18 3 BARS Ø 12

Our Bender **P32** offers to the operator the possibility to open the working cover easily, to clean / check the interior parts without difficulties. Turning disk and four long adjustable saddles in 38NCD4 special steel. As preparation of the machine for the transport, we set it on a pallet (standard measures), cover it with a stiff carton paper and with a cellophane coat, and then fix it with plastic band.

Standard Equipments

- 3 AXEL KEYS: (6 mm 8 mm 17 mm)
- 1 BUSH Ø 50 (cod. 194180)1 BUSH Ø 60 (cod. 194190)
- 1 BUSH Ø 70 (cod. 194200)1 BUSH Ø 80 (cod.194210)
- 3 BUSH HOLDING PINS (cod. 194030)
- 1 STIRRUP PIN (cod. 194040)1 SQUARE PIN (cod. 194090)
- 1 CHECKING BLOCK (cod. 195170)1 PEDAL not C.E. (cod. 181090)

