



P36

BUILT WITH A HEAVY CARRYING STRUCTURE. THE AXIAL GEARS IN FORGED AND PROCESSED STEEL AND ALL ROTARY ORGANS ARE ENCLOSED IN AN OIL BATH IN THE REDUCTION GEARBOX IN A STRONG ROLLED SECTION. AN AMBIVALENT WORKING BENCH ALLOWS ANY TYPE OF BENDING WITHOUT SHIFTING THE BAR; BESIDES, IT IS POSSIBLE TO MODIFY THE TYPE OF BEND THROUGH SHIFTING THE PEG IN THE HOLES ON THE WORKING BENCH. THE CONTROLS ALLOW STOPPING AND RECYCLING AT ANY TIME DURING THE PROCESS. LOW VOLTAGE ELECTRICAL CONTROL EQUIPMENT (24 VOLT).

P36 IS WELL PROVIDED :

- DOUBLE BENDING WITH ROTATING PLATE 350mm.
- BUSHES FROM 50mm.60mm.70mm.80m95mm.
- MOTOR HP4
- 1 CHECKING BLOCK
- 1 STIRRUP BENDING PIN
- 1 SQUARE PIN
- 3 BUSH HOLDING PINS+1 PEDAL
- BRACKET BENDER GAUGE, SPIRAL COLLER AND DUAL BENDER ARE AVAILABLE ON REQUEST
- CE SECURITY DEVICES

P36			
DIMENSIONS	86 X 85 X 95		
WEIGHT	Kg 400		
GREASE CAPACITY	Lt. 12		
BENDING CAPACITY			
	1 bar	2 bars	3 bars
R 45 KG/mm ²	36 mm	26 mm	22 mm
R 65 KG/mm ²	32 mm	24 mm	18 mm
R 80 KG/mm ²	30 mm	22 mm	16 mm