

VC52AS VC72AS

Simplify and maximize the ability for quick response



130kg Competitor
>101kg Operative weight
The lightest model in this class

Suction height **9m**
The best suction performance in the industry (9m/30ft)

Specification

	VC52AS	VC72AS	
Engine	Type	2-Cycle	2-Cycle
	Number of Cylinder	2 Cylinder	2 Cylinder
	Cooling System	Suction Water Cooled	Suction Water Cooled
	Bore x Stroke	76 x 68 mm (2.99 x 2.68 inch)	76 x 68 mm (2.99 x 2.68 inch)
	Piston displacement	617 cc (37.6 cu in)	617 cc (37.6 cu in)
	Output	30 kW (40.8 PS)	30 kW (40.8 PS)
	Fuel Type	Unleaded Gasoline (Min. 87 Octane)	Unleaded Gasoline (Min. 87 Octane)
	Fuel Tank Capacity	18 Lit (4.76 gal)	18 Lit (4.76 gal)
	Fuel Consumption	9 Lit / Hr (2.38 gal / Hr)	12 Lit / Hr (3.43 gal / Hr)
	Fuel System	Single Carburetor with Auto Choke	Single Carburetor with Auto Choke
Suction	Oil Tank Capacity	1.6 Lit (0.42 gal)	1.6 Lit (0.42 gal)
	Starting	Electric and manual	Electric and manual
	Suction System	4 Blade Rotary-vane vacuum pump (Oilless-type)	4 Blade Rotary-vane vacuum pump (Oilless-type)
	Priming System	Manual	Manual
Pump	Pump Type	Single Suction, Single Stage centrifugal pump	Single Suction, Single Stage centrifugal pump
	Suction Thread and Dia.	JIS 3" (75mm)	JIS 3" (75mm)
	Discharge Thread and Dia.	JIS 2-1/2" (65mm)	JIS 2-1/2" (65mm)
	Discharge Number	Single	Single
	Discharge Valve	Flat valve	Flat valve
Weight	Dry Weight	85 kg (187.39 lbs)	85 kg (187.39 lbs)
	Wet Weight	101 kg (222.66 lbs)	101 kg (222.66 lbs)
Dimension(mm)	Overall Length x Width x Height	700 x 620 x 730	700 x 620 x 730

NOTE JIS: Japanese Industrial Standard Thread

VC52AS Performance at suction height 3m

1250 Lit/min at 0.6MPa (6 Bar)

1000 Lit/min at 0.8MPa (8 Bar)

600 Lit/min at 1.0MPa (10 Bar)

Priming performance

2.3 sec at suction height 1 m

4.5 sec at suction height 3 m

9.2 sec at suction height 6 m

- Unmatched pumping performance
- 180 degree swinging single outlet
- Engine overheat protection sensor
- Robust and easy maintenance

VC72AS Performance at suction height 3m

1550 Lit/min at 0.6MPa (6 Bar)

1300 Lit/min at 0.8MPa (8 Bar)

950 Lit/min at 1.0MPa (10 Bar)

Performance Curve

